

PROPERTY	METHOD	SPECIFICATION LIMITS
COLOUR	ASTM D1500	2 max
CETANE NUMBER, Max	ASTM D613 - IP41	51
CETANE INDEX	EN ISO 4264	46,0
DISTILLATION, DEG.	GOST 2177	25,0
RECOVERED AT 3500 C		97,0
RECOVERED AT 2500 C		342
95% (by volume) distils at temperature		
KINEMATIC VISCOSITY AT 40 DEG. C, MM ² /C. (CST)	ASTM D445 - IP71	1.50 -4.50
SULPHUR CONTENT, mass fraction	ASTM D5453	10, Euro5
(mg/kg)		50,0 (not more)
MASS FRACTION OF POLY-AROMATIC HYDROCARBONS,%	ASTM D5186	8 MAX
HYDROGEN SULPHIDE	UOP 163	ABS
COPPER STRIPT TEST	ASTM D130	PASSED (class 1)
FLASH POINT (CLOSED CUP), DEG. C, MIN	ASTM D93 - IP34	55
COKABILITY OF 10% RESIDUE, MAX. %, CARBON RESIDUE RAMSBOTTOM, ON 10% RESIDUES.	ASTM D 189	0.3
	ASTM4530	
ASH, %, MAX.	ASTM D482, IP4	0.01
WATER CONTENT. Mg/kg	ASTM D6304	200